

	Heavy Duty Front Unload		Industrial Duty Front Unload • Front/Rear Unload				Commercial Grade Front Unload • Front/Rear Unload		
	RT516 front	RT518 front	RT616 front RT216 f/r	RT618 front RT218 f/r	RT620 front RT220 f/r	RT622 front RT222 f/r	RTX620 front RTX220 f/r	RTX622 front RTX222 f/r	RTX624 front RTX224 f/r
Floor Length	16'6"	18'6"	16'6"	18'6"	20'6"	22'6"	20'6"	22'6"	24'6"
Overall Length (box only)	19'4"	21'4"	19'4" - RT616 20'2" - RT216	21'4" - RT618 22'2" - RT218	23'4" - RT620 24'2" - RT220	25'4" - RT622 26'2" - RT222	23'4" - RTX620 24'2" - RTX220	25'4" - RTX622 26'2" - RTX222	27'4" - RTX624 28'4" - RTX224
Main Pintle Apron	667H x 4	667H x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4
Upright-Crossmember	24"	24"	24"	24"	24"	24"	16"	16"	16"
Spacing/Frame design	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded
HD Bevel Style Auger & Apron Drive	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

RT Series Specifications

Power Source	Hydraulic Drive (Opt) PTO Drive (Std) Hydraulic Cab Control Drive (Opt)	Inside Height (RT)	Standard 51" (RT) 55" w/Optional Treated Wood Top Rail Kit Add 15" for 15" Taller Side Option
Hydraulic Requirements	(20/25 gpm, 3000 psi) Front Unload	Height From Bottom of Stringers to Top of Box (RT)	70" Standard Sides 76" W/Optional Treated Wood Top Rail Kit Add 15" for 15" Taller Side Option
Augers (not spiral beaters) standard 49" sides)	2 Large 18" Diameter Augers Tapering into Box (w/ optional 64" sides)	Overall Width Conveyor Up Conveyor Down	67" W/Optional Treated Wood Top Rail Kit Add 15" for 15" Taller Side Option (with standard 36" conveyor extension) 9'2" 11'
Cross Conveyor	D662 Pintle w/Angle Cross Slat & Hold-Downs	Side Material	Clad Tuff Woven Fiberglass (White)
Discharge	Left Hand Standard-Right Hand Optional	Floor Material	Solid, High Molecular Poly Floor
Discharge Clearance Minimum (down 0)	w/36" Conveyor Extension 43.5" (on XT1600 Trailer w/riser/trk/tires) +5" for XT2200	Lower Rub Rails	Standard-Treated 2x6, Runs Full Length
Maximum (up 45)	60" (on XT1600 Trailer w/riser/trk/tires) +5" for XT2200	Emergency Stop/Cut-out	Standard
Inside Width	7'5" (RT & RTX)	Light Package	Standard w/Cord
		Truck Mount Version	Optional-Call Factory for Truck Specifications
		24" Conveyor Ext.	Optional / In Lieu of Standard 36"
		Scale Packages	Optional

RTX Series Feeder boxes available with 72"/84" inside height only. Call factory for specifications and details.