



**“9700”**

**CR P Pro**

**Precision**

**Spreading**

**Solution...**

**Crop Pro™ 9700 Premium Grade Spreading Technology**

**Multiple Spreading Heads, High-Rise Guillotine Tailgate, Dual Log Chain Aprons**

**High Volume, High Performance Spreading with our New “Crop Pro” Models**

**Spring Suspended-Steerable Axle, Cushion Hitch, Variable Speed-Gear-Driven Aprons**

*The Meyer “Crop Pro” 9700 Takes Spreading manure, Litter, Compost, Lime and Byproducts to the Next Level*



**10-gauge Steel Sides, Solid Poly Floor  
Dual Log Chain Aprons**



**36” Front Deflector, Articulating Imp. Hitch  
710/50x26.5 or 800/45x26.5 Tire Pkgs.**



**FPX100 Combination Attachment  
Ideal for Precision, Low Rate Spreading  
Hyd. Service Door / Opt. Headland Deflector**



**FPX200 Vertical Expeller Attachment  
Perfect for High Volume Spreading  
High-Wear Paddle Pkg w/Lead Edge Protection**

**Features On “Crop Pro” 9700 Models**

**1000 RPM Direct Drive, Torque Disconnect Clutch Protection, Reversing Aprons,**

**Tubular Chassis Frame, Scale Ready Equipped, Reduce Angle Drivelines**

**HD Independent Gearboxes & Shock-load Coupling Protection, Remote Grease Banks**

**Optional Features On “Crop Pro” 9700 Models**

**Highway Lighting Packages, Flat Weigh Bar Package & Athene Rate Controller,**

**1’ Straight or 2’ Flared Extensions (above LH Photo) Highway Lighting Packages**

MODEL:	9724 Tandem	9728 Tridem	9728 Quad-Axle	9732 Tridem	9732 Quad-Axle
Box Inside Length	24'	28'	28'	32'	32'
Overall Length	32' 5" w /SSTS32	36' 5" w /SSTS48	36' 5" w /SSTS64	42'5" w /SSTS48	42'5" w /SSTS64
Inside Width	90 3/4"	90 3/4"	90 3/4"	90 3/4"	90 3/4"
Overall Width	104.5"/142.5"	104.5"/142.5"	104.5"/142.5"	104.5"/142.5"	104.5"/142.5"
Box/Box w//Tires	w /800/45Rx26.5	w /800/45Rx26.5	w /800/45Rx26.5	w /800/45Rx26.5	w /800/45Rx26.5
Inside Height	46"	46"	46"	46"	46"
Overall Height w/FPX200	158.5" w /SSTS32 w /800/45Rx26.5	158.5" w /SSTS48 w /800/45Rx26.5	158.5" w /SSTS64 w /800/45Rx26.5	1152.5" w /SSTS48 w /800/45Rx26.5	1152.5" w /SSTS64 w /800/45Rx26.5
Loading Height	120.6" w /Trailer	120.6" w /Trailer	120.6" w /Trailer	120.6" w /Trailer	120.6" w /Trailer
Loading Height (12" Extensions)	132.6" w /Trailer	132.6" w /Trailer	132.6" w /Trailer	132.6" w /Trailer	132.6" w /Trailer
Loading Height (24" Extensions)	144.6" w /Trailer	144.6" w /Trailer	144.6" w /Trailer	144.6" w /Trailer	144.6" w /Trailer
Capacity-Struck/Heaped Std.	684/886 Cu. Ft.	800/1036 Cu. Ft.	800/1036 Cu. Ft.	915/1,186 Cu. Ft.	915/1,186 Cu. Ft.
Capacity-Struck/Heaped 12" Ext.	866/1068 Cu. Ft.	1012/1248 Cu. Ft.	1012/1248 Cu. Ft.	1158/1428 Cu. Ft.	1158/1428 Cu. Ft.
Capacity-Struck/Heaped 24" Ext.	1094/1360 Cu. Ft.	1280/1590 Cu. Ft.	1280/1590 Cu. Ft.	1465/1820 Cu. Ft.	1465/1820 Cu. Ft.
Weight (approximate) w/FPX200 w/o Extensions	31,780# w /800/45Rx26.5	37,530# w /800/45Rx26.5	40,490# w /800/45Rx26.5	39,950# w /800/45Rx26.5	42,910# w /800/45Rx26.5
Horse Power Required-Minimum	275 PTO HP	350 PTO HP	350 PTO HP	375 PTO HP	375 PTO HP
Apron Chains	5/8" Log Chain/2-Aprons	5/8" Log Chain/2-Aprons	5/8" Log Chain/2-Aprons	5/8" Log Chain/2-Aprons	5/8" Log Chain/2-Aprons
Slats Per Apron	43/86 Per Box	49/98 Per Box	49/98 Per Box	55/110 Per Box	55/110 Per Box
Apron Drive - Gear Drive	Single Hydraulic - Variable	Dual Hydraulic - Variable	Dual Hydraulic - Variable	Dual Hydraulic - Variable	Dual Hydraulic - Variable
Reversing Apron / In-Cab	Standard	Standard	Standard	Standard	Standard
Floor	Super Slide - Solid Poly	Super Slide - Solid Poly	Super Slide - Solid Poly	Super Slide - Solid Poly	Super Slide - Solid Poly
Box Sides	Steel - 10 gauge	Steel - 10 gauge	Steel - 10 gauge	Steel - 10 gauge	Steel - 10 gauge
High Rise Guillotine Tailgate	Standard	Standard	Standard	Standard	Standard
Front 36" Guard/Deflector	Standard	Standard	Standard	Standard	Standard
LED Rear Transport Lights	Standard	Standard	Standard	Standard	Standard
Paint Color	Black	Black	Black	Black	Black
<b>OPTIONS</b>					
Rear Attach FPX100 / FPX200	Optional	Optional	Optional	Optional	Optional
Capacity Extension 12" Straight	Optional	Optional *	Optional	Optional *	Optional
Capacity Extension 24" Flared	Optional	Optional *	Optional	Optional *	Optional
Scale Package - Variable Rate	Athene Rate Controller	Athene Rate Controller	Athene Rate Controller	Athene Rate Controller	Athene Rate Controller
Side Marker Clearance Light Pkg	Optional	Optional	Optional	Optional	Optional
Hydraulic Jack	Optional	Optional	Optional	Optional	Optional
3pt Mounted Debris Deflector	Optional	Optional	Optional	Optional	Optional
<b>TRAILERS (pull type)</b>	<b>For 9724</b>	<b>For 9728</b>	<b>For 9728</b>	<b>For 9732</b>	<b>For 9732</b>
	<b>SSTS32</b>	<b>SSTS48</b>	<b>SSTS64</b>	<b>SSTS48</b>	<b>SSTS64</b>
Trailer Frame	4x12 tubing	4x12 tubing	4x12 tubing	4x12 tubing	4x12 tubing
Axle Configuration	Tandem - Non Steer	Tridem - Steerable F&R	Quad - Steerable F&R	Tridem - Steerable F&R	Quad - Steerable F&R
	Tandem - Steerable Rear	N/A	N/A	N/A	N/A
	36,400# x 2	36,400# x 3	36,400# x 4	36,400# x 3	36,400# x 4
	<b>Fixed Spring Suspension</b>	<b>Fixed Spring Suspension</b>	<b>Fixed Spring Suspension</b>	<b>Fixed Spring Suspension</b>	<b>Fixed Spring Suspension</b>
Heavy Duty Hubs	Grease Filled - 10 Bolt	Grease Filled - 10 Bolt	Grease Filled - 10 Bolt	Grease Filled - 10 Bolt	Grease Filled - 10 Bolt
Articulating Implement Hitch	Std - Requires 1.5" or 2" pin	Std - Requires 2.75" pin	Std - Requires 2.75" pin	Std - Requires 2.75" pin	Std - Requires 2.75" pin
	Hammerstrap Style Hitch	Hammerstrap Style Hitch	Hammerstrap Style Hitch	Hammerstrap Style Hitch	Hammerstrap Style Hitch
Tire Options:	New 800/45Rx26.5	New 800/45Rx26.5	New 800/45Rx26.5	New 800/45Rx26.5	New 800/45Rx26.5
	High Floatation	High Floatation	High Floatation	High Floatation	High Floatation
	New 710/50Rx26.5	New 710/50Rx26.5	New 710/50Rx26.5	New 710/50Rx26.5	New 710/50Rx26.5
	High Floatation	High Floatation	High Floatation	High Floatation	High Floatation
Brakes (Hyd Hand Lever or Foot Pedal)	Standard (Hand Lever)	Standard (Hand Lever)	Standard (Hand Lever)	Standard (Hand Lever)	Standard (Hand Lever)
Safety Chain/SMV	Optional	Optional	Optional	Optional	Optional
Hydraulic Jack	Optional	Optional	Optional	Optional	Optional

\* Do Not Exceed Tractor Drawbar Rating.

**HD Independent Gearboxes & Shock-load Coupling Protection, Reversing Aprons, 1' Straight, or 2' Flared (above LH photo) Capacity Extensions Options Depending on Application**

**Features On "Crop Pro" 9700 Models**

**1000 RPM Direct Drive, Torque Disconnect Clutch Protection, Reversing Aprons,**

**Tubular Chassis Frame, Suspended Axle System, Highway Lighting Packages (Optional)**

**Scale-Ready Equipped (Flat Weigh Bar Package & Athene Rate Controller Optional) - Much More**